



YARRABEE & CASTLEMAINE STONE

GOLDFIELDS STRATA



STONE WALL CLADDING

GOLDFIELDS

Goldfields, as the name suggests, has that rugged look of days gone by. This beautiful blend of tones will give any project a look of permanence.

| | |
|--------------------|---|
| Components | Goldfields comes in flat pieces used for the face surface of the wall and L shaped corner pieces for the corners of the wall |
| Profile | Walling pieces are generally flat on top and bottom Corner pieces are random (organically irregular) with general flat edges |
| Dimensions: | Walling stone is random lengths 150-600mm long x 150-300mm high. Corner pieces are "L" shaped with one side 100-300mm, a return 100-200mm and a height 40-120mm |
| Thickness: | Available in 2 thicknesses: 20mm or 30mm (average) |
| Weight: | Walling flats = 70kg per m ² (30mm) or 48kg per m ² (20mm) Corners = 25kg per lineal metre (30mm) or 16kg per lineal metre (20mm) |
| Quantities: | Walling flats = 10 m ² per crate (30mm) or 15 m ² per crate (20mm) Corners = 25 lineal metres per crate (30mm) or 40 lineal metres per crate (20mm) |
| Ordering: | Sold in quantities of 1 square metre or 1 lineal metre lots Note: 1 lineal metre equates to approximately 0.3m ² of coverage Both walling flats and corners are actively stocked |
| Note: | If you are installing your stone without using grout joints, we advise adding a minimum of an additional 20-25% to account for any wastage. This will give the installer the flexibility to cut and shape the stone to achieve butt-jointed joints required for this look. Furthermore, we recommend the installer to unpack each crate of stone and utilize a mixture of the sizes provided. Smaller or unused pieces cannot be exchanged for larger ones. It is the installer's responsibility to make use of all the sizes provided. |